



US Pat. 11,079,018, 11,662,021, 12,305,755,
D927,636, D958,927, D959,598.

DIFF-TECH Fluid Service



DSM205

RAPID, versatile fluid service for driveline and oil systems.

*The **DIFF-TECH Fluid Service** is designed to remove and install petroleum-based fluids in differentials, manual transmissions, transfer cases, and other oil-based systems. Its fully pneumatic design uses shop air, helping technicians perform quick, controlled fluid service without electrical cords or complicated setup.*

- ✓ Fully pneumatic design & durable valves provide long life
- ✓ Pneumatic vacuum generator provides excellent suction, no pump failures
- ✓ Services differentials, manual transmissions, transfer cases, and oil-based systems
- ✓ Can remove old engine oil, pull fluid from transmission pans, and empty power steering reservoirs
- ✓ Dual new-fluid tanks allow multiple fluid options
- ✓ Separate hoses help reduce fluid cross-contamination
- ✓ Handheld dispenser with start/stop trigger supports controlled filling
- ✓ Large waste-fluid tank reduces the need to dump fluids during service
- ✓ Adjustable flow speeds for quick, controlled service
- ✓ Interchangeable 1/4" and 3/8" service tubes support different applications
- ✓ Clear tank design allows easy visual level monitoring
- ✓ Simple service-mode selection for fill, remove, and other functions
- ✓ Durable, well-balanced cart with easy-roll casters
- ✓ Durable black anodized panel with laser-etched notes

AffinityEG.com

AFFINITY Engineering
Group, Inc.

143 S Lincoln Dr

Troy, MO 63379

(636) 462-3314



59lbs 17" x 14" x 39"

Built for professional service environments
by **AFFINITY Engineering Group**